


# MC 421-381 Pluggable terminal block with flanges **DECA**

Pitch: 3.81mm(0.150inch)






## SPECIFICATIONS

			CUL	VDE
負載電壓	Rated Voltage	Bemessungsspannung	AC 300V	AC 300V
負載電流	Rated Current	Bemessungsstrom	10A	10A
電線線徑	Wire Size	Leitergrößen	26~16AWG	0.2~1.5mm <sup>2</sup>
塑膠本體	Housing Material	Isolierstofftyp	Polyamide66(UL94V-0)	
押線圈	Cage Clamp	Klemmkörper	Brass, Ni plated	
導電夾片	Contact	Kontakt	Phosphor bronze, Tin plated	
螺絲	Screw Size	Schraubengewinde	M2.0, steel, Ni plated	
操作溫度	Operating Temperature	Umgebungstemperatur	-40°C to + 105°C	
扭力	Torque	Anzugsmoment	3.0 lb-inch	
UL File No.	E167040			

## TABLE

Item No.	A(mm)	A(inch)
MC421-38102	17.9	0.705
MC421-38103	21.7	0.855
MC421-38104	25.5	1.005
MC421-38105	29.3	1.155
MC421-38106	33.1	1.305
MC421-38107	37.0	1.455
MC421-38108	40.8	1.605
MC421-38109	44.6	1.755
MC421-38110	48.4	1.905
MC421-38111	52.2	2.055
MC421-38112	56.0	2.205
MC421-38113	59.8	2.355
MC421-38114	63.6	2.505
MC421-38115	67.4	2.655
MC421-38116	71.2	2.805
MC421-38117	75.1	2.955
MC421-38118	78.9	3.105
MC421-38119	82.7	3.255
MC421-38120	86.5	3.405
MC421-38121	90.3	3.555
MC421-38122	94.1	3.705
MC421-38123	97.9	3.855
MC421-38124	101.7	4.005



Note:  
Screw Plating: Changes are available upon request