


ME 050-381 Header with flanges



Pitch: 3.81mm(0.150inch)





SPECIFICATIONS

| | | | CUL | VDE |
|-------------|-----------------------|---------------------|---------------------------|---------|
| 負載電壓 | Rated Voltage | Bemessungsspannung | AC 300V | AC 300V |
| 負載電流 | Rated Current | Bemessungsstrom | 12A | 10A |
| 塑膠本體 | Housing Material | Isolierstofftyp | Polyamide66(UL94V-0) | |
| 焊針 | Solder Pin | Lötstift | □0.8mm, Brass, Tin plated | |
| 操作溫度 | Operating Temperature | Umgebungstemperatur | -40°C to + 105°C | |
| PC板孔徑 | PCB Hole Diameter | Lochdurchmesser | φ1.3mm | |
| UL File No. | E167040 | | | |

TABLE

| Item No. | A(mm) | A(inch) |
|-------------|-------|---------|
| ME050-38102 | 18.0 | 0.709 |
| ME050-38103 | 21.8 | 0.859 |
| ME050-38104 | 25.6 | 1.009 |
| ME050-38105 | 29.5 | 1.159 |
| ME050-38106 | 33.3 | 1.309 |
| ME050-38107 | 37.1 | 1.459 |
| ME050-38108 | 40.9 | 1.609 |
| ME050-38109 | 44.7 | 1.759 |
| ME050-38110 | 48.5 | 1.909 |
| ME050-38111 | 52.3 | 2.059 |
| ME050-38112 | 56.1 | 2.209 |
| ME050-38113 | 59.9 | 2.359 |
| ME050-38114 | 63.7 | 2.509 |
| ME050-38115 | 67.6 | 2.659 |
| ME050-38116 | 71.4 | 2.809 |
| ME050-38117 | 75.2 | 2.959 |
| ME050-38118 | 79.0 | 3.109 |
| ME050-38119 | 82.8 | 3.259 |
| ME050-38120 | 86.6 | 3.409 |
| ME050-38121 | 90.4 | 3.559 |
| ME050-38122 | 94.2 | 3.709 |
| ME050-38123 | 98.0 | 3.859 |
| ME050-38124 | 101.8 | 4.009 |



PCB Layout

