



P/N. 3u": 3046105507

6u": 3046105607

15u": 3046105707

30u": 3046105807

50u": 3046105907

※凡標註 △ 記號者為品管管制尺寸。

MATERIALS

PLASTIC HOUSING: ENGINEERING THERMOPLASTIC
FLAMMABILITY RATING UL 94V-0.

CONTACTS: PHOSPHOR BRONZE

PLATING: GOLD PLATING OVER NICKEL IN CONTACT.

TIN PLATING OVER NICKEL IN SOLDER AREA.

SHIELD: BRASS PLATING NICKEL ALLOY.

ELECTRICAL:

CURRENT RATING: 1.5 AMPERES MAX. @ 25°C.

VOLTAGE RATING: 150 VAC MAX.

VOLTAGE: 60 VDC.

DIELECTRIC WITHSTANDING VOLTAGE:

1000VAC, RMS, 60Hz, 1MIN.

INSULATION RESISTANCE: 500 MEGOHMS MIN.

OPERATE TEMPERATURE: 0°C TO 70°C.

STORAGE TEMPERATURE: -40°C TO 80°C.

| | | | |
|--|--------------------------------|---|---|
| 設計 DR. Kathy Chung 2012/06/11 | 核准 APP. Jerry 2012/06/11 | 容許公差 .XXX ±0.10 .XX ±0.25 .X ±0.38 X ±0.50 ANG ±3° | 品名 ARTICLE 3046S 8P8C JACK W/LED(Y-G) |
| 版本說明 REVISION NOTE 更正創視圖 STAND OFF 與實品相符, 圖面發 F 版。 | | 圖號 DWG NO. 3046105607 | 單位 UNIT mm |
| | | | 比例 SCALE 2/1 1/1 |
| | | | 版數 SHEET F |
| | | | 版本 REV. F |