



MATERIALS:

- PLASTIC HOUSING: HIGH TEMP. THERMOPLASTIC
 - FLAMMABILITY RATING UL 94V-0.
 - CONTACTS: PHOSPHOR BRONZE
 - PLATING: GOLD PLATING OVER NICKEL IN CONTACT.
 - TIN PLATING OVER NICKEL IN SOLDER AREA.
 - SHIELD: BRASS PLATING NICKEL ALLOY.
- ※凡標註△記號者，為品管檢驗之尺寸。

- G/F P/N : 3050605501
- 6u" P/N : 3050605601
- 15u" P/N : 3050605701
- 30u" P/N : 3050605801
- 50u" P/N : 3050605901

設計 DR. Kathy Chung 2011/01/21	核准 APPD. Jerry 2011/01/21	容許公差 TOLERANCE .XXX ±0.10 .XX ±0.25 .X ±0.38 X ±0.50 ANG ±3°	品名 ARTICLE 3050 8P8C SMT FULL SHIELDING
版本說明 REVISION NOTE 更正金屬腳兩側尺寸16.45更正為16.20,圖面發F版.		圖號 DWG NO. 3050605601	單位 UNIT mm
KINSUN		比例 SCALE 張數 SHEET 版本 REV. 4/1 1/1 F	