



P/N:  
 6110A20030(White,Contact Area : 30u"min. Gold.  
 6110A10000(Black,Contact Area : 3u"min. Gold.  
 6110A10010(Black,Contact Area : 6u"min. Gold.  
 6110A10030(Black,Contact Area : 30u"min. Gold.  
 6110W11140(White,Contact Area : 30u"min. Gold.)限用  
 6110A60010(High Temp,White,Contact Area : 6u"min. Gold.)  
 6110A20000(White,Contact Area : 3u"min. Gold.  
 6110A30000(Blue,Contact Area : 3u"min. Gold.

**MATERIALS:**  
 HOUSING:(High Temp)Thermoplastic,UL 94V-0.  
 CONTACTS: Phosphor Bronze.  
**PLATING:**  
 (1)Gold Plating Over Nickel In Contact.  
 (2)Tin Plating Over Nickel In Solder Area.  
 SHIELD: Brass Plating Nickel.  
**MECHANICAL:**  
 DURABILITY: 1500 Mating Cycles.

RoHS COMPLIANT

※凡標註△記號者,為品管檢驗之尺寸

設計 DR. Wing 19-Nov-2010	核准 APPD. Jerry 2010-11-19	容許公差 .XXX ±0.10 .XX ±0.25 .X ±0.38 X ±0.50 ANG ±3°	TOLERANCE	品名 ARTICLE SIDE ENTRY USB B TYPE CONNECTOR(TH)
版本說明 REVISION NOTE -----依E302-1011049新增規格-----				圖號 DWG NO. 6110A20000
				單位 UNIT mm
				比例 SCALE 1/3
				張數 SHEET 1/1
				版本 REV. F