


## Rohs Compliant






## <u> 1</u>4 9.20



RECOMMEND P.C.B. LAYOUT



MATERIALS:

HOUSING:Thermoplastic,UL 94V-0,Black.

CONTACTS: Phosphor Bronze.

PLATING:

(1)Gold Plating Over Nickel In Contact.

(2)Tin Plating Over Nickel In Solder Area.

SHIELD: Steel Plating Tin. (Matte Sn)


MECHANICAL:

DURABILITY: 5000 Mating Cycles.

P/N:

6140A11000(Contact Area: $3\mu$ "min.Gold.) 6140A11010(Contact Area:6μ"min.Gold.)

6140A11030(Contact Area:30 μ"min.Gold.)



## ※凡標註/記號者,為品管檢驗之尺寸。

設計 DR. 核准 APPD. Wing Jerry 2010-03-12	容許公差 .XXX .XX .XX	TOLERANCE ±0.10 ±0.25 ±0.38	品名 ARTICLE Mini USB AB Type Connector			
版本説明 REVISION NOTE依E302-1002045設變案	X ANG	±0.50 ±3°	圖號 DWG NO.	614	0A1100	)0
<u>KINSUN</u>			單位 UNIT mm	比例 SCALE 1/3	張數SHEET 1/1	版本 REV. A