



Pin Hole Layout
(Jack Bottom View)

11.	Barrel 3.5φ	Brass	1	Nickel Plated
10.	Barrel 2.5φ	Brass	1	Nickel Plated
9.	Housing	PBT+15%G	1	Black Color
8.	Earth Terminal	0.3T Phosphor Bronze	1	Silver Plated
7.	Ring Spring	0.25T Phosphor Bronze	1	Silver Plated
6.	Tip Spring	0.25T Phosphor Bronze	1	Silver Plated
5.	Tip Spring	0.25T TiCuR1-M-EH	1	Silver Plated
4.	Break Terminal	0.3T Bronze	1	Silver Plated
3.	Break Terminal	0.3T Bronze	2	Silver Plated
2.	Ring Spring	0.2T TiCuR1-M-EH	1	Silver Plated
1.	Earth Terminal	0.25T Phosphor Bronze	1	Silver Plated
NO.	Description	Material	Q'TY	Finish

RoHS
Compliant

For Reference
僅供參考

SPECIFICATIONS:

Contact Resistance : 30mΩ max
 Insulation Resistance : 100MΩ min. at DC 500V
 Dielectric Withstanding Voltage: AC 500V for one minute
 Remark: ▲: The Most Important Dimension

S.C. PRECISION INDUSTRIAL CO., LTD.
旭全

DATE DWN CHKD APVD MANAGER

12.10.2005

PART NAME : 3.5φ PHONE JACK

PART NUMBER : SCJ375RONASOB00G

VERSION:3.0

TOLERANCE :±0.3mm UNLESS OTHERWISE SPECIFIED

UNIT:mm



SCALE:1/1