



□ GAP. 0.25mm (Max.)

SPECIFICATIONS:
 Contact Resistance : 30mΩ max
 Insulation Resistance : 100MΩ min. at DC 500V
 Dielectric Withstand Voltage : AC 500V for one minute
 Remark: ▲: The Most Important Dimension

6.	Housing	PBT+30%G.U194V-0	1	White Color
5.	Spring	0.3T Phosphor Bronze	1	Light Tin 80"(min.) Over Ni 50u"(min.)
4.	Rear Shell	0.3T Iron	1	Nickel Plated
3.	Front Shell	0.3T Bronze	1	Nickel Plated
2.	Terminal	0.25T Phosphor Bronze	4	Gold Flash Over 50u"(min.) Nickel, Tin Lead
1.	Terminal	0.25T Phosphor Bronze	4	Gold Flash Over 50u"(min.) Nickel, Tin Lead
E	Description	Material	Q'TY	Finish

PART NAME : USB A-TYPE SOCKET
 PART NUMBER : SCU102RFN1W1000

S. C. PRECISION INDUSTRIAL CO., LTD.

TOLERANCE : ±0.3mm UNLESS OTHERWISE SPECIFIED	UNIT: mm	SCALE: 1/1	VERSION: 2.0	DATE	DWN	CHKD	APPD	MANAGER
1	2	3	4	5	6	7	8	9



Pin Hole Layout
(Jack Bottom View)

2002.5.24
 支取