

## Stiftlängen und Veredelungen für therm. geriss. Vierkantstift 0,635mm

*Pin Length Options & Platings for electro-strictioned Square Pins 0,635mm*

Stiftlänge (mm) Pin Length (mm)	Längen-Code Length Code	Au Flash Au Flash	0.25µm Au 0.25µm Au	2.5µm Sn 2.5µm Sn
9,50	9,5	00	10	50
<b>10,80</b>	<b>11</b>	00	10	50
<b>11,30</b>	<b>12</b>	00	10	50
<b>12,60</b>	<b>13</b>	00	10	50
13,30	13,3	x <sup>1</sup>	10	50
<b>13,90</b>	<b>14</b>	00	10	50
<b>14,70</b>	<b>15</b>	00	10	50
15,50	15,5	x <sup>1</sup>	10	x <sup>1</sup>
15,70	15,7	x <sup>1</sup>	x <sup>1</sup>	50
16,40	16,4	x <sup>1</sup>	10	50
<b>17,70</b>	<b>16</b>	00	10	50
18,30	18,3	x <sup>1</sup>	10	x <sup>1</sup>
18,70	18,7	x <sup>1</sup>	10	x <sup>1</sup>
<b>19,80</b>	<b>17</b>	00	10	50
20,60	20,6	x <sup>1</sup>	10	50
<b>21,60</b>	<b>18</b>	00	10	50
<b>22,80</b>	<b>19</b>	00	10	50
<b>24,90</b>	<b>20</b>	00	10	50
26,00	26,0	x <sup>1</sup>	10	50
<b>26,70</b>	<b>21</b>	00	10	50
27,40	27,4	x <sup>1</sup>	10	x <sup>1</sup>
<b>29,00</b>	<b>22</b>	00	10	50
<b>30,80</b>	<b>23</b>	00	10	50
32,00	32,0	00	10	50
35,20	35,2	x <sup>1</sup>	x <sup>1</sup>	50
36,00	36,0	x <sup>1</sup>	10	x <sup>1</sup>
<b>37,80</b>	<b>24</b>	00	10	50
<b>40,80</b>	<b>25</b>	00	10	50
43,00	43,0	x <sup>1</sup>	x <sup>1</sup>	50
<b>46,30</b>	<b>46,3</b>	x <sup>1</sup>	x <sup>1</sup>	50

x<sup>1</sup> > 200k Pin MOQ

Für gestanzte/geprägte Kontakte sind Stiftlängen von 6,5 bis 72,5mm in allen Veredelungen auf Anfrage verfügbar.  
For stamped/formed contacts pin lengths from 6,5 up to 72,5mm are available on request in all platings.