



Frequency Range:

6.00MHz to 80.00MHz

Features:

- High Reliability & Low Cost Unit
- Extended Temperature Available
- Lead-free Type



QUARTZ
CRYSTALS

■ Standard Specifications

Item	Value
Frequency Range	6.00 to 80.00MHz
Frequency Tolerance	±20ppm
Frequency Tolerance over Temperature range	±50ppm
Operating Temperature Range	-10 °C to +60 °C (other operating range also available)
Operable Temperature Range	-40 °C to +85 °C
Equivalent Series Resistance (ESR)	Please refer to the ESR Table
Drive Level	50µW
Load Capacitance	8pF
Ageing	±5ppm/year

■ ESR Table

Frequency Range (MHz)	Mode	Standard ESR (Ohm)
6 to 8	AT Cut Fund.	150
8 to 9	AT Cut Fund.	100
9 to 10	AT Cut Fund.	60
10 to 11	AT Cut Fund.	50
11 to 13	AT Cut Fund.	40
13 to 50	AT Cut Fund.	30
26 to 80	3rd Overtone.	100

Note:

1. Manufacturer reserves the right to change the specification and content of this product for improvement without notification.
2. Custom specification is welcome. Please contact our sales representative for further details.
3. If the crystal is intended for applications which have direct impact on human life and properties, and require a high degree of reliability and safety concerns, customers must provide full information such as but not limit to the application, electrical and reliability specification at the inquiry beginning stage.
4. Customers have to agree to the "Guideline for handling crystal units" and "Standard Terms and Condition of Sales" which is printed this catalog before placing orders to our company or our distributors. There are also unpredictable factors such as applied condition, oscillation margin and etc and customers must check them beforehand. In case of queries, please do not fail to send inquiry to our company before ordering.

