



- NOTES**
- 1.MATERIALS:
 - 1.1HOUSING&NUT: ENGINEERING THERMOPLASTIC UL 94V-0.
 - 1.2CONTACTS: PHOSPHOR BRONZE
 - 1.3GASKET: SILICON
 - 2.FINISH:
 - 2.1CANTACT: GOLD PLATING OVER NICKEL.
 - 3.NOTES.1:請參閱附件EN-3352-B0010與EN-3352-B0011
 - 4.NOTES.2:螺帽安裝扭力值範圍為 17~18kg-cm
 - 5.WATERPROOF RATE:IP67, UNMATED
 - 6.OPERATING TEMPERATURE -40~+80°C

		△C			
Shield	Blue/White	藍/白	10	Twist	
	Blue	藍	9		
	Green/White	綠/白	8	Twist	
	Green	綠	7		
	Orange/White	橙/白	6	Twist	
	Orange	橙	5		
	Red/White	紅/白	4	Twist	
	Red	紅	3		
	Brown/White	棕/白	2	Twist	
	Brown	棕	1		
Conn	Wire Color		Housing		
	Pin Out				

設計 DR. Leon 2014/07/02	核准 APPD. Marco 2014/07/02	容許公差 .XXX ±0.10 .XX ±0.25 .X ±0.38 X ±0.50 ANG ±3°	TOLERANCE	品名 ARTICLE 3352加Wafer(線長8cm)
版本說明 REVISION NOTE		圖號 DWG NO. 3352E02010		單位 UNIT mm
-----修正φ20.60公差-----		比例 SCALE 張數 SHEET 1/1		
				版本 REV. H