



2.5Ø PHONE JACK BUSHING GUIDANCE

No.	Bushing Figure	Ordering Code	Bushing Construction			Typical S.C. Series No.
			Material	Thread	Metal Ring	
1		M0	Metal	×	×	SCJ218M0 SCJ220M0
2		M1	Metal	M4×P0.5	×	SCJ210M1 SCJ211M1 SCJ214M1 SCJ218M1 SCJ220M1
3		P0	Plastic	×	×	SCJ224P0, SCJ225P0 SCJ228P0, SCJ230P0 SCJ232P0, SCJ234P0 SCJ237P0, SCJ238P0 SCJ240P0, SCJ260P0
4		R1	Metal	×	With Metal Ring 1)O.D. : 5.0mm 2)Position : Bushing Outside	SCJ224R1
5		R2	Metal	×	With Metal Ring 1)O.D. : Ø4.0mm 2)Position : Bushing Outside	SCJ224R2 SCJ225R2
6		R5	Metal	×	With metal bushing cap	SCJ246
7		R7	Plastic	×	×	SCJ236

Nut			Unit : m/m		
Fig. I			Fig. II		

Order Code No.	Fig.	Shape	Description			Dimension		
			Thread	Material	Plating	Dia. A	Dim. B	Dim. C
1	Fig. I	Round	M4 × P0.5	Brass	Nickel	Ø 6.0	1.5	0.9
2	Fig. II	Hexagonal	M4 × P0.5	Brass	Nickel	7.0	1.5	-

S. C. PRECISION INDUSTRIAL CO., LTD.