





6.3Ø PHONE JACK

SCJ620 / SCJ624 SERIES

	P/N	Dimension (m/m)	Pin Hole Layout (Jack Bottom View)							
 SCJ 620R0	SCJ 620									
 SCJ 620P5										
 SCJ 624R0	SCJ 624									
 SCJ 624P5										
Schematic Code										
										
	A	B	C	D	E	F	G	H	I	J

Feature

The SCJ620/SCJ624 series is designed for PC board mounting type with low profile mounting center 6.5mm.

Construction

1. Housing : Thermoplastic
2. Contact : Phosphor bronze
3. Terminal : Brass / Copper alloy

Specification

1. Withstanding voltage :
AC 500V, 60Hz for 1 minute
2. Insulation resistance :
100MΩ (min.) at 500V DC
3. Contact resistance :
30mΩ (max.)
4. Insertion & Extraction force :
Initial : 0.5 to 3.0kgs
After life test : 0.3 to 3.0kgs
5. Life test :
5,000 cycles unloading (20-30 cycles per minute)
6. Humidity test is kept in 90-95%(RH) for 96 hours.

Ordering Information

SCJ620 ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐

① ② ③ ④ ⑤ ⑥ ⑦ ⑧

- ① : Series No.
SCJ620 / SCJ624
- ② : Bushing type R0, P5 (See page C-3 for details)
- ③ : Metal ring plating ("N" is standard)
N : Nickel G : Gold flash
0 : No plating (no metal ring)
- ④ : Schematic (See above drawing)
A-J
- ⑤ : Terminal plating ("S" is standard)
T : Tin S : Silver G : Gold flash
- ⑥ : Nut & washer option (See page C-4)
0 : Without nut & washer
1 : With nut (M12×P1.0) & washer
- ⑦ : Housing color option
B : Black (Standard)
Other colors option are available
- ⑧ : Special option
00 : No special option

S. C. PRECISION INDUSTRIAL CO., LTD.